



(人為損壞除外)

CREPOW® 合作成果

全球最新科技

快馬系列

FORCEARC 253



僅重  
10Kg

**PowerFactor** 0.75  
**Efficiency** >85%  
**Cooling** AF  
**Insulation Class** H  
**Protection Class** IP23

- 重工業專用，重量輕巧
- 調節功能齊全，可令焊工起弧容易
- 可加裝內置防電擊裝置，符合地盤安全
- 特別適合戶內戶外焊接大型結構
- 合乎建築署及勞工處電弧焊機之安全條例
- 內置防電擊裝置

## Heavy Industrial Use

- Input Voltage: 380~440V 50/60Hz
- Heavy Duty Cycle
- Voltage Reduction Device
- Tig Mode  
capable of welding with Lift Tig Mode
- Extra Functions  
'Hot Start', 'Anti-sticking' and 'Air Force' built in
- Protection  
Equipped with temperature, voltage and current sensors for high protection
- Voltage Reduction Device (Optional)

## 規格 Specification:

入力電壓 Power Supply Voltage (V)	頻率 Frequency (Hz)	輸入功率 Rated Input Power (KW)	輸入電流 Rated Input Current (A)	暫載率 Duty Cycle 40°C 10min	空載電壓 No Load Voltage (V)	焊接電流調節 Welding Current Range (A)
3~380V +10%	50/60 Hz	8.5 KW	16.5	60% 250A 100% 200A	65V	10 ~ 250 A
淨重 Net Weight (Kg)	尺寸 Dimensions (mm)	焊接焊條尺寸 Electrode Diameter	焊接焊條類型 Electrode Type			
10	375 x 190 x 335mm	1.6 ~ 5.0	6013, 7018 etc.			

